## In the Claims:

- 1. (Currently Amended) A transistor, comprising:
  - a workpiece;
  - a doped region disposed in the workpiece, the doped region including a dopant species;
- a doped gate dielectric disposed over the doped region of the workpiece, the doped gate dielectric including the dopant species, wherein the doped gate dielectric comprises about 50 Å or less of Si<sub>3</sub>N<sub>4</sub>, Al<sub>2</sub>O<sub>3</sub>, Ta<sub>2</sub>O<sub>5</sub>, HfO<sub>2</sub>, TiO<sub>2</sub>, HfSiO<sub>x</sub>, ZrO<sub>2</sub>, or ZrSiO<sub>x</sub>;
  - a gate disposed over the gate dielectric; and
- a source region and a drain region formed in at least the doped region of the workpiece, wherein the source region, drain region, gate, and doped gate dielectric comprise a transistor.
- 2. (Original) The transistor according to Claim 1, wherein the dopant species comprises at least one Group V, VI or VII element.
- 3. (Currently Amended) The transistor according to Claim 2, wherein the dopant species comprises nitrogen or fluorine.
- 4. (Original) The transistor according to Claim 1, wherein the doped region comprises a thickness of about 100 Å or less.
- 5. (Original) The transistor according to Claim 1, wherein the dopant species fills vacancies in the atomic structure of the gate dielectric.

- 6. (Currently Amended) The transistor according to Claim 1, wherein the doped gate dielectric comprises a high k dielectric material material. or an oxide, and wherein the gate comprises a semiconductor material or a metal.
- 7. (Canceled)
- 8. (Original) The transistor according to Claim 1, further comprising a thin insulating layer disposed between the gate dielectric and the doped region of the workpiece.
- 9. (Original) The transistor according to Claim 8, wherein the thin insulating layer comprises a thickness of about 10 Å or less.
- 10. (Original) The transistor according to Claim 9, wherein the thin insulating layer comprises silicon dioxide or silicon oxynitride.
- 11. (Original) The transistor according to Claim 1, wherein the workpiece comprises a silicon-on-insulator (SOI) wafer.
- 12-36. (Canceled)
- 37. (New) The transistor according to Claim 2, wherein the dopant species comprises nitrogen.

- 38. (New) The transistor according to Claim 1, wherein the doped gate dielectric comprises an oxide.
- 39. (New) The transistor according to Claim 1, wherein the gate comprises a semiconductor material.
- 40. (New) The transistor according to Claim 1, wherein the gate comprises a metal.
- 41. (New) A transistor, comprising:
  - a workpiece;
  - a doped region disposed in the workpiece, the doped region including a dopant species;
- a doped gate dielectric disposed over the doped region of the workpiece, the doped gate dielectric including the dopant species;
  - a metal gate disposed over the gate dielectric; and
- a source region and a drain region formed in at least the doped region of the workpiece, wherein the source region, drain region, gate, and doped gate dielectric comprise a transistor.
- 42. (New) The transistor according to Claim 41, wherein the dopant species comprises at least one Group V, VI or VII element.
- 43. (New) The transistor according to Claim 42, wherein the dopant species comprises fluorine.

- 44. (New) The transistor according to Claim 42, wherein the dopant species comprises nitrogen.
- 45. (New) The transistor according to Claim 41, wherein the doped gate dielectric comprises a high k dielectric material.
- 46. (New) The transistor according to Claim 45, wherein the doped gate dielectric comprises about 50 Å or less of Si<sub>3</sub>N<sub>4</sub>, Al<sub>2</sub>O<sub>3</sub>, Ta<sub>2</sub>O<sub>5</sub>, HfO<sub>2</sub>, TiO<sub>2</sub>, HfSiO<sub>x</sub>, ZrO<sub>2</sub>, or ZrSiO<sub>x</sub>.
- 47. (New) The transistor according to Claim 41, further comprising a thin insulating layer disposed between the gate dielectric and the doped region of the workpiece, wherein the thin insulating layer comprises a thickness of about 10 Å or less.
- 48. (New) The transistor according to Claim 44, wherein the thin insulating layer comprises silicon dioxide.
- 49. (New) The transistor according to Claim 44, wherein the thin insulating layer comprises silicon oxynitride.
- 50. (New) The transistor according to Claim 41, wherein the workpiece comprises a silicon-on-insulator (SOI) wafer.

- 51. (New) The transistor according to Claim 41, wherein the doped gate dielectric comprises an oxide.
- 52. (New) The transistor according to Claim 41, wherein the gate comprises a semiconductor material.
- 53. (New) The transistor according to Claim 41, wherein the gate comprises a metal.